

MDPE/HDPE Test Plugs for Pressure Testing to 6bar



Product Specification

Available for Pipe Sizes from 12mm up to 40mm internal diameter.

For use with small bore copper, steel or MDPE/HDPE piping.

Suitable for Pressure Testing up to 6bar.

Suitable also for telecommunications, refrigeration, air conditioning, heating, process plant and food manufacturing.

“Double Seal” plugs can be supplied to order.

Steel components are zinc plated to 90 hours salt spray test.

Carries the Horobin name – quality guaranteed.

It is the responsibility of the installer / operator to make sure the maximum allowed back pressure of HOROBIN pipe stoppers are not exceeded.

Please see maximum allowed back pressures in the table below

Part No.	Pipe Size Internal Nominal Diameter		Will Fit Pipes With Internal Diameter		Minimum Insertion into Pipe	Overall length	Contact length	Diameter of waterway	Maximum allowable back pressure	Approx. Weight
	Metric	Imperial	Minimum	Maximum						
73811	12mm	1/2"	12mm	16mm	66mm	110mm		4mm	50psi	40gm
73821	19mm	3/4"	19mm	26mm	66mm	110mm		6mm	50psi	50gm
73831	25mm	1"	25mm	37mm	66mm	110mm		6mm	50psi	70gm
73841	32mm	1 1/4"	31mm	39mm	66mm	110mm		6mm	50psi	90gm
73851	40mm	1 1/2"	38mm	48mm	66mm	110mm		6mm	30psi	130gm